

Concert Club V Series

Monitor



SM15V



CM15V



SM12V



CM12V



SM10V



CM10V

Monitor performance, reliability, and exteriors optimally matched to the Club V S series front-of-house speakers and subs.

Perfect monitors for Club V C Series systems.

- Painsstaking selection of parts and components, optimized wooden enclosures, and a thorough reevaluation of speaker capacity take sonic performance to a new level.
- Dual phone jacks and dual Speakon connectors for input and parallel connection.
- Protection circuit prevents excessive tweeter input due to acoustic feedback or other causes.
- Durable exterior with a carpeted surface, arced steel grille, and large metal handles for improved portability.
- Angled cabinet for easy monitor placement.
- All monitor models are equipped with a pole socket for use with speaker stands.
- The YSProcessing (Yamaha Speaker Processing) switch provided on the EMX series powered mixers and P series amplifiers enhances matching for even greater sonic impact.

Concert Club V Series


GENERAL SPECIFICATIONS

Model	SM15V/CM15V	SM12V/CM12V	SM10V/CM10V
Type	2-way bass-reflex		
Frequency range (-10dB)	55Hz-16kHz	60Hz-16kHz	70Hz-20kHz
Nominal coverage	40Hx90V		40Hx60V
Nominal impedance	8Ω		
Power rating	NOISE	250W	175W
	PGM	500W	350W
	MAX	1000W	700W
Sensitivity (1W,1m)	99dB SPL		97dB SPL
Component	LF	15" cone	10" cone
	HF	Horn + 2" voice coil driver	
Connectors	1/4" phone jack x 2, SPEAKON Neutrik NL4MP x 2		
Dimensions (W x H x D)	719 x 483 x 343mm (28.3" x 19.0" x 13.5")	632 x 414 x 351mm (24.9" x 16.3" x 13.8")	560 x 353 x 277mm (22.0" x 13.9" x 10.9")
Weight	SM15V: 28.0kg (61.7lbs)/CM15V: 28.8kg (63.5lbs)	SM12V: 21.4kg (47.2lbs)/CM12V: 21.8kg (48.1lbs)	SM10V: 13.4kg (29.5lbs)/CM10V: 13.3kg (29.3lbs)


DIMENSIONS

unit : mm

SM15V/CM15V



SM12V/CM12V



SM10V/CM10V

