YAMAHA WATER MIDI EXPANDER

OWNER'S MANUAL

YAMAHA YMEE

Thank you for purchasing the Yamaha YME8 MIDI (Musical Instrument Digital Interface) Expander. The YME8 is a parallel box designed especially for Digital Interfacing. In order to gain the proper performance from this unit, be sure to read this instruction booklet thoroughly before using it.

CAUTION

- If for some reason you should use any other AC adapter than the one provided with the YME8 (the PA-1), be sure it is the following type:
 DC6 12V, + - Special care must be taken that adapters of reverse polarity are not used.
- When finished using the YME8, do not forget to put both selector switches at OFF, and make sure the red indicator turns off.
- Do not use this unit near a window where the unit may be exposed to direct sunlight, or in any other extremely hot locations, as this may impair its performance.
- Take good care of the unit; be careful not to drop it or treat it roughly in any way.
- Irreparable damage may result from opening the YME8 cabinet or attempting to alter the internal circuitry. If there is a problem, contact your nearest Yamaha dealer.

SPECIFICATIONS

MIDI IN :

: 2

MIDI THRU

: 2 lines of 4

Selector Switches

 $(W \times H \times D)$

: Input Selectors (2)

Power

: External DC 6 - 12V 100mA

Dimensions

: 164mm x 30mm x 72mm

Weight

 $(6-1/2'' \times 1-1/8'' \times 2-7/8'')$


Accessory

: 503g (1.1 lbs.) : AC Adapter (PA-1)

USAGE

Use the selector switches to choose the desired combination of input.

EXAMPLE 1) With this set up, the keyboard/sequencer connected to MIDI IN 1 will control all eight keyboards connected to the MIDI THRU.



EXAMPLE 2) With this set up, the keyboard/sequencer connected to MIDI IN 1 controls the keyboards connected to MIDI THRU 1 to 4. And, the keyboard/sequencer connected to MIDI IN 2 controls the keyboards connected to MIDI THRU 5 to 8.

